

	Overspeed Governor ALJO/GERVALL		 PEW Electrical Distributors Ltd.
	<i>Enquiry Form</i>		
<i>Company</i>		<i>Date</i>	
<i>Project / Reference</i>		<i>Your email</i>	



Sheave	Rope	Nominal Rated Speed	Tripping Speed
Ø200 mm	Ø 6 - 6.5 mm	≤ 1,75 m/s	0,30—2,20 m/s
Ø300 mm	Ø 6 - 6.5 - 8 mm	≤ 2,15 m/s	0,40—2,70 m/s



<i>Installation Type:</i>	Machine Room MRL	<i>Quantity:</i>	<i>Model Reference:</i>
<i>Sheave Diameter:</i>	Ø200 mm Ø300 mm	<i>Tripping Direction:</i>	Descent only Ascent and descent
<i>Rated speed:</i>		<i>Activation Type:</i>	Centrifugal Trigger
	Manual reset (1 NC)		
<i>Overspeed switch:</i>	Automatic Reset		1 NC + 1 NO 2 NC + 1 NO
	Remote reset		2 NC 24 V DC (4,2 A) 2 NC 230 V AC (0,5 A)
<i>Remote Tripping System:</i> <i>(MRL Installations)</i>	No 24 V DC (1,9 A) 48 V DC (1 A) 190 V DC (0,2 A) 230 V DC (0,2 A)	<i>Encoder:</i>	Yes No
		<i>UCM system for +A3</i> <i>(24 VDC):</i>	Yes No
<i>Related Products</i>			
<i>Protection Cover:</i>	Yes	<i>Tension Pulley:</i>	Floor mounted Guide mounted
			
<i>Remarks:</i>			

All Overspeed Governors are supplied with rope-out protection. For more information, visit www.gervall.com